

Acrylic Based Topcoat, specially formulated that closes all the pores of its granules



Description

Sealing compound for decorative gravel floors. After the curing is complete, a transparent film layer is formed.

Packaging Types 10kg 20kg

Pallet Description

10kg	50pcs X 10kg	Total 500kg
20kg	25pcs X 20kg	Total 500kg

Consumption Depend Granule Size (1m²)

0,4 - 0,8 mm	300 gr	2 - 3 mm	800 gr
0,8 - 1,2 mm	450 gr	2 - 4 mm	950 gr
1,5 - 2,5 mm	600 gr	3 - 5 mm	1.150 gr

Features / Benefits

- Forms a hydrophobic layer on the surface
- High scratch resistance on the surface coating
- Excellent adhesion on to stone carpet surface
- After application of stone carpet easy to apply on both vertical and horizontal surfaces
- Resistant to UV rays, and pollution
- Durable, even after exposure to extremely high and extremely low temperatures (-10 °C, + 40 °C)

Application Areas

- Indoors
- Showrooms, Living areas
- Shops, Supermarkets
- Public buildings, Offices
- Schools and colleges

Technical Data

Potlife: ± 30 minutes (20 °C)
Drying Time: 7 hours (25 °C)
Walkable After: 24 hours

Application Procedure

Easy to apply with a glass wipers.
Never apply with a brush!